LINKFONE®

Linkfone V-732

Professional Two-Way Radio

RELIABLE RANGE, EVERYWHERE YOU GO.



CORE FEATURE	HIGHLIGHT
Durable Antenna	High-durability flexible whip antenna for clear signal transmission
Emergency Alarm	Dedicated emergency alert function for rapid team notification
3000mAh Battery	High-capacity Li-ion rechargeable battery for extended field operation
VOICE Scrambler	Built-in voice scrambler for enhanced communication privacy
Included Kit	Battery, Charging Base, Antenna, Belt Clip

SPECIFICATIONS

PARAMETER	SPECIFICATION
GENERAL	
Frequency	446–446.2 MHz
Channel Capacity	16 channels
Power Supply	7.4V DC
Dimensions	135mm × 55mm × 27mm
Weight	168g
Operating Temp	−20°C to +60°C
Battery Capacity	3000mAh; Li-ion
TRANSMITTER	
RF Power	0.5W
Channel Spacing	12.5 kHz
Frequency Stability	±1.5ppm
Modulation Deviation	≤2.5kHz / ≤5kHz
Spurious & Harmonics	−36dBm <1GHz, −30dBm >1GHz
FM Hum & Noise	−40dB / +40dB
Adjacent Channel Power	≥60dB / 70dB

PARAMETER	SPECIFICATION
Audio Response (300–3000Hz)	+3dB − 3dB
Audio Distortion (300–3000Hz)	≤5%
RECEIVER	
Sensitivity (12dB SINAD)	≤0.25μV / ≤0.35μV
Adjacent Channel Selectivity	−60dB / −70dB
Audio Output @ <5% Distortion	1W
Audio Distortion	5%
Radiated Spurious Emissions	−54dBm
Intermodulation Rejection	−70dB
Spurious Response	65dB